

M900

VoIP cordless DECT multicell base station



Multicell System



Power over Ethernet



Security (TLS & SRTP)



OTA Updates

Benefits

- Up to 4,000 base stations
- Up to 16,000 handset
- DECT and LAN synchronisation
- No DECT manager required
- Compatible to existing handsets⁽¹⁾
- Over-the-air software updates for handsets
- Repeater support⁽²⁾
- PoE and power adapter support
- TLS encryption
- DSP module support
- Wallmountable
- Local, XML and LDAP phone book support

DECT

- Frequency bands:
 - 1880-1900 MHz (EU)
 - 1920-1930 MHz (US)
- Output power: EU < 250 mW, USA < 140 mW
- Protocols: DECT, DECT 6.0
- Seamless handover and roaming
 - Handover using DECT or LAN synchronisation (IEEE1588)
- Wideband audio
- Authentication/encryption of base and handset

Range

- Indoors: Up to 50 meters
- Outdoors: Up to 300 meters (for indoor use only)

Multicell System

- Up to 16,000 registered handsets in the same network in multicell setup
- Up to 4,000 registered base stations in a multicell setup
- Up to 100 repeaters in a multicell setup⁽²⁾
- Up to 8 narrowband or 4 wideband calls per base station in multicell setup
- Up to 10 narrowband or 5 wideband calls per base station in single-cell set-up
- Common phonebook with up to 3000 entries
- List of registered handsets
- Compatible to M700 running the same software version

Audio, Codecs

- G.722 (5 channels; 4 in multicell operation)
- G.711 A-law, μ -law,
- G.726 (10 channels; 8 in multicell operation)
- Codec negotiation, codec switching
- A900 enables
 - G.729 (10 channels, 8 multicell operations)
 - BV32 (10 channels, 8 multicell operations)
 - Opus (8 channels)

User Interfaces

- LED status indication, multicolor
- Reset key
- Web interface

Installation

- Positioning:
 - Wall mounting
 - Ceiling mounting
- Remote software updates via HTTP/ HTTPS/TFTP
- Automatic loading of settings via HTTP/ HTTPS/ TFTP
- Completely configurable through Web interface
- Static IP, DHCP support
- NTP (Network Time Protocol)
- Secure provisioning and authentication with Mutual TLS through individual certificate issued by Snom CA
- Compatible handset feature RSSI tool, no additional measurement equipment needed

Hardware Specifications

- Weight: approx. 306g
- Dimensions: approx. 144x140x35 mm (LxWxD)
- Antenna diversity (two internal omni-directional antennas for better transmission and reception)
- Power: Power over Ethernet (PoE) IEEE802.3af Class 2. If PoE is not available, the A5 PoE injector can be used (not included)⁽³⁾, Power adapter available⁽⁴⁾
- Ethernet connector: RJ 45
- LAN interface: 10/100 BASE-T IEEE 802.3
- Colour: White
- Part Number: 00004426 (EU), 00004441 (US)

Network

- HTTP and HTTPS
- LLDP
- IEEE 802.1Q
- TLS 1.2



- (1) Compatible handsets:
- Snom M25, Snom PN 00003987 (EU),
00003988 (US)
 - Snom M65, Snom PN 00003969
 - Snom M70, Snom PN 00004423
 - Snom M80, Snom PN 00004424
 - Snom M85, Snom PN 00004189
 - Snom M90, Snom PN 00004426

- (2) Compatible DECT Repeater:
- Snom M5, Snom PN 00003839

Accessories:

- (3) If PoE is not available, the Snom A5 PoE Injector (Phihong, model POE16R -1AFG, 56V) can be used to power and connect the M900.
Snom PN: 00004065
- (4) Power adapter 5V/2A EU, Snom PN 00004439
Power adapter 5V/2A US, Snom PN 00004440
DSP codec module A900, Snom PN 00004445

Series Overview



M25



M65



M70



M80



M85



M90